



US005768532A

# United States Patent [19]

Megerian

[11] Patent Number: 5,768,532  
[45] Date of Patent: Jun. 16, 1998

[54] **METHOD AND DISTRIBUTED DATABASE  
FILE SYSTEM FOR IMPLEMENTING SELF-  
DESCRIBING DISTRIBUTED FILE OBJECTS**

## FOREIGN PATENT DOCUMENTS

522488 1/1993 European Pat. Off. .  
WO96/07149 3/1996 WIPO .

[75] Inventor: **Mark Gregory Megerian**, Rochester,  
Minn.

*Primary Examiner*—Mehmet B. Geckil  
*Attorney, Agent, or Firm*—Joan Pennington

[73] Assignee: **International Business Machines  
Corporation**, Armonk, N.Y.

[57] **ABSTRACT**

[21] Appl. No.: **664,706**

[22] Filed: **Jun. 17, 1996**

[51] Int. Cl.<sup>6</sup> ..... **G06F 12/00**

[52] U.S. Cl. .... **395/200.75**; 370/409; 707/103;  
707/104; 395/200.31

[58] **Field of Search** ..... 395/220.31, 200.47,  
395/133, 62, 200.75; 711/216; 707/10,  
103, 104; 370/409

[56] **References Cited**

## U.S. PATENT DOCUMENTS

5,301,337	4/1994	Wells et al. ....	395/800
5,371,675	12/1994	Greif et al. ....	364/419.1
5,381,534	1/1995	Shi ....	395/200.33
5,542,078	7/1996	Martel et al. ....	395/600
5,551,027	8/1996	Choy et al. ....	395/600
5,581,760	12/1996	Atkinson et al. ....	395/700
5,687,363	11/1997	Qulid-Aissa et al. ....	395/604
5,701,462	12/1997	Whitney et al. ....	395/610

A method and apparatus are provided for implementing self-describing file objects. A node group is created for defining multiple computer systems for storing data. A hash algorithm for applying to data records is identified. A partition distribution map for distributing data to each of the multiple computer systems utilizing a set of predetermined hash algorithm results and remote system information for each of the multiple computer systems are identified. A file object is created in each of the multiple computer systems. Each the file objects includes the hash algorithm, the partition distribution map, and the remote system information. A data record is inserted into one of the distributed file objects by receiving the data record, applying the hash algorithm to the received data record, comparing the hash algorithm result with the partition distribution map to identify the particular computer system for the data record, utilizing the system information to establish connection to that system. The file objects are fully self-describing, eliminating the need for additional objects to be addressed, opened, paged into memory or the like.

**16 Claims, 4 Drawing Sheets**

